

2.1 MP 1080P 4in1 IR Dome Camera

FEATURES

- 4-in-1 HDCVI / HDTV/AHD / CVBS optional output
- Full HD resolution 1920 x 1080P with CMOS sensor
- Ultra low illumination 0.02Lux
- Up to 300M long distance and high speed real time monitoring
- OSD menu control up the coaxial cable (UTC)
- Low light and high dynamic range
- Day/Night (ICR), AWB, AGC, BLC, DNR, D-WDR, Smart IR
- Lightning protection
- Strong water-proof housing, IP66
- 18 pcs IR Leds, IR distance 20-30 meters
- 2.8 mm lens



TECHNICAL SPECIFICATIONS

CAMERA

| | |
|--------------------|--|
| Image Sensor | 1/2.9" 2.1 Mega pixels CMOS |
| Chipset | FH8536H+F33 |
| Effective Pixels | 1936(H)×1096 (V) |
| Video Resolution | 1080P@25/30fps |
| Electronic Shutter | AUTO, 1/25 - 1/50,000s |
| Min. Illumination | 0.02Lux@F1.2(AGC ON), 0Lux IR on |
| Video System | PAL/NTSC |
| Video Output | 1 channel, HDCVI / HDTV/AHD/CVBS , adjustable |
| Video Switch | DIP SWITCH |
| Day/Night | Auto/Color/(B/W)/EXT |
| WDR | Digital WDR |
| White Balance | AWB/ATW/Indoor/Outdoor/Manual |
| AGC/BLC | Support |
| DNR | 2D NR |
| OSD Menu | Multiple languages OSD menu control up the coaxial cable (UTC) |

IR LED

| | |
|-------------|----------------------|
| IR Led | 12 pcs ARRAY IR Leds |
| IR Distance | 20-30M |

LENS

| | |
|--------------|-------------------|
| Focal length | 2.8 mm fixed lens |
|--------------|-------------------|

GENERAL

| | |
|-------------------|--------------------------|
| Power Supply | 12 VDC ± 10% |
| Power Consumption | <5W |
| Operating Temp. | -20°C-(+60)°C, 10%-90%RH |