

## HYU-813

SF-T943-5E4N1 / SF-T941A-5P4N1 / SF-T941AG-5P4N1

HYUNDAI

### 4 in 1 fixed dome HYUNDAI NEXT GEN PRO series with 30m Smart IR for outdoor



- 4 in 1 fixed dome HYUNDAI NEXT GEN PRO series with 30m Smart IR for outdoor
- 5MP CMOS
- 5MP @ 20ips resolution Switchable 4-in-1 video output
- 2.8mm (85.5 °) fixed lens
- ICR filter
- AWB, AGC, BLC, HLC, Digital WDR, 2D-DNR
- It incorporates a microphone
- Coaxial audio
- IP67
- 3AXIS
- 12V DC.



Reference / Model

HYU-813 / SF-T943-5E4N1 / SF-T941A-5P4N1 / SF-T941AG-5P4N1

**4 in 1 fixed dome HYUNDAI NEXT GEN PRO series with 30m Smart IR for outdoor****Reference / Model****HYU-813 / SF-T943-5E4N1 / SF-T941A-5P4N1 / SF-T941AG-5P4N1****Features**

5 megapixel CMOS  
5MP (2560x1944) at 20 ips  
2.8mm fixed lens  
OSD menu control via coaxial cable (UTC)  
Digital WDR, 3D-DNR  
Smart IR up to 30 meters  
Includes microphone  
Supports coaxial cable audio transmission (only compatible with ZVR HYUNDAI with audio)  
4-in-1 video output  
Protection degree IP67

**Specifications**

5 megapixel CMOS sensor  
Digital resolution: 5MP (2560x1944)  
Images per second:  
TVI: 5MP (20 ips), 4MP (25/30 ips), 1080P (25/30 ips)  
AHD: 5MP (20 ips), 4MP (25/30 ips)  
CVI: 4MP (25/30 ips)  
CVBS: PAL / NTSC  
Switchable 4-in-1 video output (HDCVI, HDTVI, AHD, CVBS)  
Removable mechanical filter  
0.01 lux F1.2 (color) / 0 lux IR On  
Smart IR: 30 meters  
2.8mm fixed lens  
85.5 ° (H), 63.7 ° (V), 110.7 ° (D) angle of view  
Automatic and manual white balance  
Automatic gain control  
Backlight compensation: BLC, HLC  
Digital WDR  
2D digital noise reduction  
Brightness and sharpness adjustment  
Mirror mode  
Includes microphone  
Coaxial Audio  
Power: 12V DC (± 25%)  
Consumption: Max. 3.7W  
-40 ° C ~ + 60 ° C operating temperature  
Relative humidity: <90% (without condensation)  
Protection degree IP67  
Metal housing  
Dimensions: Ø82.6x90 x 79.37 mm  
Weight: 290g  
3AXIS: 0 ° ~ 355 ° (PAN), 0 ° ~ 75 ° (TILT), 0 ° ~ 355 ° (Rotation)