

HYU-991

SF-XVR6116-1FACE / SF-XVR6116AS-1FACE

HYUNDAI

HYUNDAI 5-in-1 16-channel ZVR



- HYUNDAI 16-channel 5-in-1 ZVR
- H.265 Pro+/H.265+ formats
- 16 BNC 4MP + 2 IP 6MP channels
- 4MP@15fps recording
- Simultaneous HDMI and VGA 1080P outputs
- Bi-directional audio, audio over coaxial
- Video analytics
- Supports 1 HDD 10TB, 1 RJ45 Gigabit, 1 RS485, 2 USB, Onvif.



Reference / Model

HYU-991 / SF-XVR6116-1FACE / SF-XVR6116AS-1FACE

5-in-1 ZVR with 16 HD analogue channels + 2 IP channels

5 technologies: IP cameras, HDCVI, HDTVI, AHD and Analogue CVBS

Connectable to H.265 Pro+, H.265 Pro, H.265, H.264+, H.264, H.264 IP cameras

16 BNC inputs (supports coax)

2 IP inputs up to 6MP (16+2)

Simultaneous HDMI (1080P) and VGA (1080P) outputs

BNC video output

Audio channels: 1 RCA input / 1 RCA output

Bi-directional audio: via RCA audio channel 1

Supports coaxial audio (16 inputs)

Recording resolution: 4MP Lite, 3MP, 1080P, 1080P Lite, 720P, WD1, 4CIF, VGA, CIF

Main stream with 1080P Lite mode off:

4MP stream: 4M Lite (15 fps), 1080P Lite, 720P, WD1, 4CIF, VGA, CIF (25/30 fps).

HYUNDAI 5-in-1 16-channel ZVR

Reference / Model	HYU-991 / SF-XVR6116-1FACE / SF-XVR6116AS-1FACE
	3MP Stream: 3MP, 1080P, 720P, VGA, WD1, 4CIF, CIF (15 fps)
	1080P stream: 1080P, 720P (15 fps), VGA, WD1, 4CIF, CIF (25/30 fps)
	720P stream: 720P, VGA, WD1, 4CIF, CIF (25/30 fps)
	Main stream with 1080P Lite mode enabled: 4M Lite, 3MP (15 fps), 1080P Lite, 720P Lite, WD1, 4CIF, VGA, CIF (25/30 fps)
	Secondary stream: WD1, 4CIF (12 fps), CIF (25/30 fps)
	16-channel synchronised playback
	Internal capacity for 1 SATA HDD up to 10TB (sold separately)
	Intelligent search
	Supports multiple VCA (Video Content Analytics) events for both analogue and smart IP cameras
	Deep learning-based motion detection 2.0 is enabled by default for all analogue channels, can classify people and vehicles and minimise false alarms caused by lights or objects such as leaves
	Perimeter protection of up to 4 perimeter protection channels with person/vehicle analysis
	Auto-adaptive RJ45 Ethernet (10/100/1000M) network interface
	Network protocols: TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS
	Remote access for up to 128 users
	Onvif support
	P2P in the cloud, DDNS DEMES, Push and zero channel
	Connections: 1 USB 2.0, 1 USB 3.0, 1 RS485 Half Duplex
	Power supply: 12V DC, 2A
	Power consumption: ≤24W
	Operating temperature: -10°C ~ +55°C
	Relative humidity: 10~90%.
	Dimensions: 315 (W) x 45 (H) x 242 mm (desktop)
	Weight: ≤2 kg